



Kvaser PCICanx II HS/HS

EAN: 73-30130-00343-9

The Kvaser PCICanx II HS/HS is a dual channel, high speed CAN (controller area network) interface board for the PCI-X and PCI bus. It features an on-board microcontroller for offloading your main CPU and galvanic isolation for protection against voltage spikes.

Major Features

- Quick and easy plug-and-play installation - no switches.
- Compliant with PCI 2.3.
- The board fits in both 3.3V PCI-X and 3.3V and 5V PCI busses.
- Fully software compatible with the discontinued PCICan II boards.
- Communicates with the PC through a fast DPRAM.
- CAN Controller is a Renesas M16C.
- Supports CAN 2.0 A and 2.0 B (active).
- High-speed ISO 11898 compliant driver circuits, supports bit rates up to 1 Mbit/s.

- Industry-standard 9-pin D-SUB connectors.
- Pin assignment according to CiA-DS102.
- 16 MHz CAN oscillator frequency.
- Galvanic isolation between the CAN-controller and the CAN-driver.
- The Kvaser PCICanx II family boards can optionally be delivered with exchangeable CAN drivers, supporting e.g. single-wire CAN.
- Includes free of charge low profile bracket.

Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.

TECHNICAL DATA - KVASER PCICANX II HS/HS

ERROR FRAME DETECTION	Yes
RUGGED	No
ON-BOARD BUFFER	Yes
STATUS	Active
WEIGHT (G)	100.0
ERROR FRAME GENERATION	Yes
TIMESTAMP RESOLUTION (US)	N/A
EMBEDDED SCRIPT	No
ON-BOARD RX BUFFER	N/A
# OF CAN CHANNELS	2
MAXIMUM BITRATE (KBPS)	1000
WIDTH (MM)	120
ERROR COUNTERS READING	Yes
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
CONNECTOR	DSUB 9
CERTIFICATIONS	CE,RoHS
CLOCK SYNC	No
LENGTH (MM)	95
SOUND	No
CASING MATERIAL	-
HEIGHT (MM)	20
ON-BOARD TX BUFFER	N/A
IP CLASS	N/A
NETWORK CHANNEL(S)	2 x CAN HS
MSGRATE TX MAX	8000
OPERATING SYSTEM	Win Vista,Win 8,Win 7,Win XP
API, LICENCED	None



Kvaser PCICanx II HS/HS

MINIMUM BITRATE (KBPS)	N/A
GALVANIC ISOLATION	Yes
PC INTERFACE	PCI
MSGRATE RX MAX	14000
API, FREE	Kvaser API, J2534, RP 1210
SILENT MODE	Yes

The information herein is subject to change without notice